ALLTE/NP

www.alltemp.ca



Universal Air Switch

The NS2 Switch has a glass-filled polycarbonate housing containing a sensing diaphragm and an integral snap-acting switch with three male 90° quick-connect terminals. The switch can be actuated by a pressure or vacuum air flow or the differential between two air flows. The field adjustable set point range of this switch is 0.10"w.c. to 10.0"w.c. Using the switch accessories contained in this kit, the NS2 switch can be applied to a wide variety of residential and light commercial HVAC applications.

OPERATION

Operating Range - .10"w.c. to 10"w.c. Max Pressure Rating - 14"w.c. Mounting - vertical or custom angle Operating Temp. - -40°C to 88°C Sample Line Connections - Black positive, Gray negative Sample Medium - Air and by-products of combustion that will not degrade silicone or polycarbonate Product Life - 100,000 Cycles



Kit Includes:

- SOLENOID
- 1/4" COMPRESSION × 18" MPT WITH FILTER SCREEN
- 3/16" BARB × 1/8" MPT
- 1/8" MPT × 1/4" COMPRESSION
- 1/8" MPT × 5/16" COMPRESSION
- 1/4" INSERT (FOR PLASTIC TUBE)
- 1/4" DELRIN SLEEVE (FOR PLASTIC TUBE)

TO REVERSE FLOW, REMOVE BRACKET SCREWS AND TURN 180°

ALLTEMP

Universal Humidifier Solenoid

Introducing the first universal solenoid replacement. This one unit will replace over 32 different direct OEM solenoids in the field. Just wrench in the appropriate fittings on the inlet and outlet, and even change water flow from left to right tor right to left. Replaces many Aprilaire, General, Honeywell, Skuttle, and many other models for a fraction of the cost.

CROSS REFERENCE

Aprilaire - #4040 General - #990-53 Honeywell - #32001639-002 Skuttle - #A01-0814-148