

RESCUE® Motors Permanent Split Capacitor Condenser Fan 5.6" Diameter, Totally Enclosed Air Over (TEAO)




APPLICATIONS:

Commercial and Residential Condensing Units. Can replace a range of horsepower application and a variety of mounting styles.

FEATURES:

- High 158°F (70°C) Or 140°F (60°C) Ambient Designs
- Automatic Reset Thermal Overload Protector
- Designed For Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For Rheem® Or Trane® Units
- 48" Leads
- Extended Mounting Studs
- Ball Bearings
- Reversible Rotation
- High Efficiency Design
- Continuous Duty, Air Over
- Reversible Rotation



RESCUE® Condenser Motors available in 158°F (70°C) ambient ratings!

Catalog Number	List Price	HP	RPM	Max. Ambient	Speed Tap (RPM)	Volts	Cap. MFD @ 208V	Cap. MFD @ 230V	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes
★ 5464	\$142	1/3	825	140°F(60°C)	High (825)	208-230	10	7.5	1.9	5	5.3	10.3	18	1
		1/4			High (835)		10	7.5	1.5					
		1/5			Low (825)		10	7.5	1.2					
		1/6			Low (825)		10	7.5	1.0					
★ 5464H	\$145	1/3	825	158°F(70°C)	High (825)	208-230	10	7.5	1.9	5	5.3	10.3	18	1
		1/4			High (835)		10	7.5	1.5					
		1/5			Low (825)		10	7.5	1.2					
		1/6			Low (835)		10	7.5	1.0					
★ 5462	\$109	1/3	1075	140°F(60°C)	High (1110)	208-230	7.5	5	2.6	5	4.6	9.6	14	1
		1/4			High (1135)		7.5	5	2.5					
		1/5			Low (1110)		7.5	5	2.0					
		1/6			Low (1125)		7.5	5	1.8					
★ 5462H	\$114	1/3	1075	158°F(70°C)	High (1110)	208-230	7.5	5	2.6	5	4.6	9.6	14	1
		1/4			High (1135)		7.5	5	2.5					
		1/5			Low (1110)		7.5	5	2.0					
		1/6			Low (1125)		7.5	5	1.8					
★ 5465	\$138	1/2	1075	140°F(60°C)	High (1110)	208-230	12.5	10	3.0	5	5.3	10.3	19	1
		1/3			High (1135)		12.5	10	2.2					
		1/4			Low (1110)		12.5	10	1.6					
		1/6			Low (1125)		12.5	10	1.3					
★ 5465H	\$148	1/2	1075	158°F(70°C)	High (1110)	208-230	12.5	10	3	5	5.3	10.3		1
		1/3			High (1135)		12.5	10	2.2					
		1/4			Low (1110)		12.5	10	1.6					
		1/6			Low (1125)		12.5	10	1.3					
★ 5482H	\$160	3/4	1075	158°F(70°C)	High (1115)	208-230	15	15	4	5	6.3	11.875		1
		1/2			High (1145)		15	15	2.8					
		1/3			Low (1115)		15	15	1.9					
		1/4			Low (1145)		15	15	1.4					

460 Volt Rescue Condenser Fan Motors

Catalog Number	List Price	HP	RPM	Max. Ambient	Speed Tap (RPM)	Volts	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes
★ 5480H	\$240	1/2	1075	158°F(70°C)	High (1095)	460	10	1.3	5	5.562	11.1	19	1
		1/3			High (1145)			0.9					
		1/4			Low (1100)			0.7					
		1/5			Low (1140)			0.5					
★ 5481H	\$260	3/4	1075	158°F(70°C)	High (105)	460	15	2.2	5	6.3	11.857	22	1
		1/2			High (1135)			1.3					
		1/3			Low (1070)			1.1					
		1/4			Low (1130)			0.7					

Note 1 Side Shell & Lead End Mounting Screws Included In Carton

★ — Suggested Distributor Stock Item