

RESCUE® Motors Permanent Split Capacitor Direct Drive Fan & Blower, 5.6" Diameter, Open, Air Over




APPLICATIONS:

Commercial and Residential Air Handlers and Furnaces. Can replace a range of horsepower applications and a variety of mounting styles.

FEATURES:

- Extended Mounting Studs
- Designed For Use With 370v Capacitors
- Class B Insulation
- 36" Leads
- High Efficiency Design®
- Includes Side Shell Holes For Rheem® Units
- Continuous Duty, Air Over
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- 2.5" Dia. Hub Rings Included



Catalog Number	List Price	HP	Cool Speed Tap (Approx. RPM)	Heat Speed Tap (Approx. RPM)	Volts	Bearings	Cap MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wgt.	Notes	
★ 5469	\$170	1/3	High (825)	Med-Hi (825)	208-230	Slv	7.5	2.4	2.2		4.6	6.74	17	1	
		1/4	Med-Hi (825)	Med-Lo (825)				7.5	1.7						
		1/8	Med-Lo (825)	Low (825)				7.5	0.9						
★ 5460	\$115	1/2	High (1100)	Med-Hi (1050) or Med-Low (825)	115	Slv	10	7.3	5.0	5.4	4.8	9.8	15	1, 2	
		1/3	High (1120)	Med-Hi (1090) or Med-Low (1030)				5	6.9						
		1/4	Med-Hi (1125)	Med-Low (1090) or Low (1010)				5	5.5						
		1/5	Med-Low (1110)	Low (1060)				5	3.6						
		1/6	Low (1085)	Low (1085)				5	2.8						
★ 5461	\$118	1/2	High (1100)	Med-Hi (1050) or Med-Low (825)	208-230	Slv	10	3.6	5.0	5.4	4.8	9.8	15	1, 2	
		1/3	High (1120)	Med-Hi (1090) or Med-Low (1030)				5	3.5						
		1/4	Med-Hi (1125)	Med-Low (1090) or Low (1010)				5	2.8						
		1/5	Med-Low (1110)	Low (1060)				5	1.9						
		1/6	Low (1085)	Low (1085)				5	1.3						
★ 5470	\$138	3/4	High (1110)	Med-Hi (1080) or Med-Low (1010)	115	Ball	20	8.1	5.0	6.6	6.1	11.6	22	1	
		1/2	High (1130)	Med-Low (1090) or Low (1035)				10	6.6						
		1/3	Med-Hi (1150)	Med-Low (1130) or Low (1100)				10	4.6						
		1/4	Med-Low (1150)	Low (1130)				10	3.8						
		1/5	Low (1140)	Low (1140)				10	3.1						
★ 5471	\$141	3/4	High (1110)	Med-Hi (1080) or Med-Low (1010)	208-230	Ball	20	3.8	5.0	6.6	6.1	11.6	21	1	
		1/2	High (1130)	Med-Low (1090) or Low (1035)				10	3.7						
		1/3	Med-Hi (1150)	Med-Low (1130) or Low (1100)				10	2.5						
		1/4	Med-Low (1150)	Low (1130)				10	1.8						
		1/5	Low (1140)	Low (1140)				10	1.7						

Note 1 Screws For Shell Mounting Included In Carton

Note 2 For 1/3 To 1/6 HP, if more air flow is needed, a 7.5 mfd capacitor may be used.

★ — Suggested Distributor Stock Item