

# MODEL VX6000C CENTRAL VACUUM POWER UNIT



Designed for homes up to 6,000 square feet (557.4 m<sup>2</sup>) or consumers looking to step up in features. This power unit is specially designed with a 2-stage motor and delivers 550 air watts of power. It's the most powerful power unit in its class. The unique oval shape offers space saving advantages and efficient cyclonic filtration.

### FEATURES

- Internal sound suppression system makes it the quietest power unit in its class
- Progressive full lights tell the homeowner when to empty the debris pail
- Easy access door for cyclonic filter maintenance
- Oversized debris pail handles make for quick and easy pail removal
- Large 7 U.S. gallons (26.5 litres) debris pail. Typically needs emptying only every 6 months!
- Dual vacuum air intakes allow for connecting to the tubing line from the right side, left side or both
- Six foot (1.8 m) long power cord
- cUL Listed

Limited Lifetime Warranty

### SPECIFICATIONS

Motor . . . . .	.2-Stage Universal Bypass
Horsepower . . . . .	.2.4 @ Full Open Orifice
Voltage . . . . .	.120 VAC
Airflow at 2" (50.8 mm) opening . . . . .	.135 CFM (63.7 L/s)
Water Lift . . . . .	.130" (3.3 m)
Air Watts . . . . .	.550
Switch on Power Unit . . . . .	.Yes
Utility Valve with Power Unit . . . . .	.Yes
Recommended Circuit . . . . .	.20 Amps
Primary Filtration . . . . .	.Self-Cleaning Permanent Fabric with Non-Stick Teflon Inner Liner, HEPA Rated Media, Microban Treated
Capacity . . . . .	.7 U.S. Gallons (26.5 Litres)
Secondary Filtration . . . . .	.Screen
cUL Listed . . . . .	.Yes
Housing . . . . .	.Corrosion Resistant Flame Retardant Engineered Thermoplastic
Power Unit Dimensions . . . . .	.11.5" D x 17.5" W x 39" H (292 mm D x 445 mm W x 991 mm H)



Broan-NuTone Canada; Mississauga, Ontario www.broan.ca 877-896-1119

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by <span style="float: right;">Date</span>