



- ▶ High colour rendering index of 90
- ▶ A superior quality lighting that enhances the natural colour of the surrounding objects
- ▶ TCLP compliant
- ▶ One System extended lamp/ballast warranty

Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	PS=Program Start ballast			PRS=Program Rapid Start ballast		
						Rated life PS/PRS (3 hrs)	Initial lumens (lm)	Mean lumens (lm)	Nominal length in. (mm)	Efficacy (lm/W)	Case qty
T12 Dia. : 1 1/2 in. (38 mm)											
900 series											
64251	F40T12/41K/9/RS/G13/STD	40	G13	4 100	90	24 000	2 500	2 500	48 (1 220)	63	30
64252	F40T12/50K/9/RS/G13/STD	40	G13	5 000	90	24 000	2 250	2 250	48 (1 220)	56	30
64253	F40T12/65K/9/RS/G13/STD	40	G13	6 500	90	24 000	2 250	2 250	48 (1 220)	56	30
T12 U-bent Dia. : 1 1/2 in. (38 mm)											
900 series											
64255	FB40T12/41K/9/U6/RS/G13/STD	40	G13	4 100	90	24 000	2 500	2 500	22.6 (574)	63	12
64256	FB40T12/65K/9/U6/RS/G13/STD	40	G13	6 500	90	24 000	2 250	2 250	22.6 (574)	56	12



OUTDOOR



INDOOR



WARRANTY



CRI 90+



TCLP



RECYCLABLE



ONE SYSTEM WARRANTY

T12 & T12 U-Bent Lamps