

Perfect for the light cooking habits, the BU3 range hood models provide the quality you expect and the value you demand.

SIZE	WHITE	WHITE WITH BLACK CONTROL	STAINLESS	GREASE FILTER (replacement)	CHARCOAL FILTER
24 in.	BU324WW	-	-	BP29	41F
30 in.	BU330WW	BU330WH	BU330SS	BP29	41F

PERFORMANCE				
Duct Orientation	Size	Damper	Sones on high speed	CFM on high speed
Vertical - Rectangular	3¼ in. x 10 in.	Included	7.5	190
Horizontal - Rectangular	3¼ in. x 10 in.	Included	7.5	190

FEATURES	
Control type	Rotary switch, variable speed
Delay off	no
Filter Clean Reminder	no
Heat Sentry™	no
Lighting	2-level 75-watt bulb (not included)
Grease Filter	Aluminum (Qty. 1)
ENERGY STAR®	no
Recirculation	Charcoal filter sold separately


AC INPUT
120 V, 60 Hz - 2.5 AMPS

OPTIONAL ACCESSORIES	
3¼ in. x 10 in. to 6-in. Round Duct Transition	411
7-in. Round Damper	BP87
7-in. Round Adapter Plate	SR680508

MOUNTING HEIGHT
18 in. to 24 in. from cooktop to bottom of hood


LIMITED WARRANTY
1-year
(See installation manual for full warranty text.)

FOR INDOOR USE ONLY



* Center point for 7" round installation.

Dimensions shown in inches.



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

99045920A